




DisplayPort, HDMI, DVI and VGA KVM switches

Uniclass offers various audio video and KVM products such as DisplayPort, HDMI, DVI and VGA KVM switches.

One of the features is True Transparent USB (TTU) which enables KVM switch to operate with traditional keyboards and mice.

For more information about Uniclass,
please contact our sales department.



KVM

Switches

Uniclass

2 Port DVI-I Dual-Link Dual Monitor USB KVM Switch with audio

The BD1124 Dual-Link DVI KVM Switch is specifically designed for sharing two monitors between two multimedia computers with Dual Head display [2 x DVI]. With the BD1124, you can fully control two Dual Head PCs using only one keyboard, mouse and Dual DVI monitors/Flat Panel Displays. This Dual Monitor DVI KVM Switch supports both digital video (2560 x 1600) and analog video (2048 x 1536).

- 2 port Dual-Link DVI KVM switch
- 7.1 surround sound support
- Independent switching of audio/hub/pc ports
- True Transparent USB (TTU) emulation technologie



Technical specifications

Connections (computer)	: 3,5 mm jack female (x6), DVI 24+5-pin female (x2), USB B female (x1)
Connections (console)	: 3,5 mm jack female (x6), DVI 24+5-pin female (x2), USB B female (x1)
Max. resolution @ 60Hz	: 2560 x 1600
Video signal	: DVI
Video support	: HDCP
DVI specification	: DVI-I Dual Link
Other signals	: Digital audio
Control method	: Button, Hot-key
Power supply	: External power supply
Included	: 2 x Audio cables, 2 x USB cables, 4 x DVI-D cables, 1 x power adapter
Number of consoles	: 1

Type no.	Manufacturer no.	Description
BD1124	AL-702D	2 port DVI-I Dual Link & View KVM switch

DisplayPort/USB KVM switch+audio

- True Transparent USB
- Switches DisplayPort and audio

Technical specifications

Connections (computer)	: 3,5 mm jack female (x2), DisplayPort female (x1), USB B female (x1)
Connections (console)	: 3,5 mm jack female (x2), DisplayPort female (x1), USB A female (x4)
Max. resolution @ 60Hz	: 2560 x 1600
Video signal	: DisplayPort
DisplayPort specification	: Not specified by manufacturer
Other signals	: Analog audio
Control method	: Button, Hot-key
Power supply	: External power supply
Included	: Power supply
Number of consoles	: 1



UNICLASS

Type no.	Manufacturer no.	Description
AB7983	AP-204A	DisplayPort, USB and audio switch 1:4
AB7981	AP-202A	DisplayPort, USB and audio switch 1:2

HDMI / USB KVM switch

- True Transparent USB
- Including 4x USB (type a to b) and 4 HDMI cables

Technical specifications

Connections (computer)	: HDMI A (full-size) female (x1), USB B female (x1)
Connections (console)	: HDMI A (full-size) female (x1), USB A female (x2)
Max. resolution @ 60Hz	: 1920 x 1200
Video signal	: HDMI
Video support	: EDID, HDCP
HDMI specification	: HDMI 1.4
Control method	: Button, Hot-key, Remote control (IR), Software
Power supply	: External power supply
Included	: Power supply and software
Number of consoles	: 1



UNICLASS

Type no.	Manufacturer no.	Description
AB7979	AI-EP04A	HDMI and USB switch 1:4

Compact HDMI / USB KVM switch

- True Transparent USB

Technical specifications

Connections (computer)	: HDMI A (full-size) female (x1), USB B female (x1)
Connections (console)	: HDMI A (full-size) female (x1), USB A female (x4)
Max. resolution @ 60Hz	: 1920 x 1200
Video signal	: HDMI
Video support	: HDCP
HDMI specification	: HDMI 1.3
Other signals	: USB 2.0 - HighSpeed (Enhanced)
Control method	: Button, Hot-key, Remote control (IR)
Power supply	: External power supply
Included	: Power supply
Number of consoles	: 1



UNICLASS

Type no.	Manufacturer no.	Description
AB7977	AI-CP02A	HDMI and USB switch 1:2

DVI / USB KVM switch+audio

- True Transparent USB

Technical specifications

Connections (computer)	: 3,5 mm jack female (x2), DVI-I Single Link female (x1), USB B female (x1)
Connections (console)	: 3,5 mm jack female (x2), DVI-I Single Link female (x1), USB A female (x4)
Max. resolution @ 60Hz	: 1920 x 1200
Video signal	: DVI
Video support	: DDC, HDCP
DVI specification	: DVI-I Single Link
Other signals	: Analog audio
Control method	: Button, Hot-key
Power supply	: External power supply
Included	: Power supply
Number of consoles	: 1



UNICLASS

Type no.	Manufacturer no.	Description
AB7969	AD-202A	DVI, USB and audio switch 1:2
AB7971	AD-204A	DVI, USB and audio switch 1:4

DVI / USB cable KVM switch

Technical specifications

Max. resolution @ 60Hz	: 1920 x 1200
Control method	: Hot-key, Remote control (wired), Software
Power supply	: USB powered
Included	: Power supply, software and integrated connection cables

AB7966

Connections (computer)	: 3,5 mm jack male (x4), DVI 24+5-pin female (x2), USB A male (x2)
Connections (console)	: 3,5 mm jack female (x2), DVI 24+5-pin female (x1), USB A female (x2)
Video signal	: DVI
Video support	: EDID
DVI specification	: DVI-D Single Link
Other signals	: Analog audio



UNICLASS

Type no.	Manufacturer no.	Description
AB7966	UDV-TA2	DVI/USB cable KVM switch 2 ports

Compact DVI / USB KVM switch+audio

- True Transparent USB

Technical specifications

Connections (computer)	: DVI-D Single Link female (x1), USB B female (x1)
Connections (console)	: 3,5 mm jack female (x2), DVI-D Single Link female (x1), USB A female (x4)
Max. resolution @ 60Hz	: 1920 x 1200
Video signal	: DVI
Video support	: DDC, HDCP
DVI specification	: DVI-D Single Link
Other signals	: Analog audio
Control method	: Button, Hot-key
Power supply	: External power supply, USB powered
Included	: Power adapter
Number of consoles	: 1



UNICLASS

Type no.	Manufacturer no.	Description
AB7963	AD-CP02A	DVI, USB and audio switch 1:2

VGA / PS/2 - USB 19" KVM switch

- Robust and durable design
- Cascadable
- Manage up to 128 computers by cascading multiple switches

Technical specifications

Connections (computer)	: VGA HD D-sub 15-pin male (x1)
Connections (console)	: PS/2 female (x2), VGA HD D-sub 15-pin female (x1)
Max. resolution @ 60Hz	: 2048 x 1536
Video signal	: VGA
Other signals	: RS-232
Control method	: Button, Hot-key, On Screen Display (OSD)
Power supply	: External power supply
Included	: Power supply and daisy-chain cable
Number of consoles	: 1



UNICLASS

Type no.	Manufacturer no.	Description
AB7984	PRIMA T4	VGA/PS/2 - USB 19" KVM switch 4 ports
AB7988	PRIMA T8	VGA/PS/2 - USB 19" KVM switch 8 ports
AB7996	PRIMA T16	VGA/PS/2 - USB 19" KVM switch 16 ports

KVM System Cable for AB7984, AB7988 and AB7996

System cable for professional KVM switch, AB7984, AB7988 and AB7996.



Type no.	Manufacturer no.	Description
AK7980	CAB-2067-1.8M	VGA / PS/2+USB KVM connection cable 1.80 m
AK7981	CAB-2067-3M	VGA / PS/2+USB KVM connection cable 3.00 m
AK7982	CAB-2067-5M	VGA / PS/2+USB KVM connection cable 5.00 m

VGA / USB KVM switch

Technical specifications

Max. resolution @ 60Hz	: 2048 x 1536
Control method	: Button, Hot-key, Software
Power supply	: Bus powered
Included	: Power supply, software and integrated connection cables

AB7964

Connections (computer)	: 3,5 mm jack male (x4), USB A male (x2), VGA HD D-sub 15-pin male (x2)
Connections (console)	: 3,5 mm jack female (x2), USB A female (x2), VGA HD D-sub 15-pin female (x1)



Type no.	Manufacturer no.	Description
AB7964	USB-TA2	VGA, USB and audio switch 1:2

Adder

Adderview pro DisplayPort KVM switch

KVM switch for switching between 4 computers with DisplayPort, USB and audio signals.

- Two extra USB sockets to connect other devices next to mouse and keyboard
- True Emulation USB 2.0 technology
- Independent simultaneous device selection

Technical specifications

Connections (computer)	: 3,5 mm jack female (x1), DisplayPort female (x1), USB B female (x1)
Connections (console)	: 3,5 mm jack female (x1), DisplayPort female (x1), USB A female (x4)
Max. resolution @ 60Hz	: 2560 x 1600
Video signal	: DisplayPort
Video support	: DDC, EDID
DisplayPort specification	: Not specified by manufacturer
Other signals	: Analog audio, USB 2.0 - HighSpeed (Enhanced)
Control method	: Button, Hot-key
Power supply	: External power adapter
Included	: Power supply
Number of consoles	: 1



Type no.	Manufacturer no.	Description
AD2000	AV4PRO-DP-IEC	DisplayPort, USB and audio switch 1:4