

HDM T/N			Outer Mbl d: B-029-019-A	Outer Mbl d: B-011-019-A	REV	DATE	CHANGE BEFORE	CHANGES	DRAW
			Outer Mbl d: B-029-019-B		△	09. 11. 28			

CONN 1 HDMI 19 MALE

CONN 2 HDMI 19P MALE

PART NO.:	LENGTH	TOLERANCE	RESI STANCE
82584	1M 1000mm)	& 20mm	2ohm
82583	2M 2000mm)	& 40mm	2ohm
82454	3M 3000mm)	& 60mm	3ohm
82455	5M 5000mm)	& 100mm	4ohm

Electronic Test:

1. Contact Resistance : 4ohm max
2. Insulation Resistance : 10M ohm min
3. Hi - Pot : 300V DC/10ms
4. All Materials With RoHS Standard
5. 100% test when it is open and short

High Speed HDMI Cable with Ethernet male/male 1m

4 043619 825844

Product no.:82584

High Speed HDMI Cable with Ethernet male/male 2m

4 043619 825837

Product no.:82583

High Speed HDMI Cable with Ethernet male/male 3m

4 043619 824540

Product no.:82454

High Speed HDMI Cable with Ethernet male/male 5m

4 043619 824557

Product no.:82455

NO	NAME	DESCRIPTION	UNIT	QTY
8	COPPER FOIL	25*48MM	pcs	2
7	OUTER MOLD	30P PVC COLOR: BLACK	g	12
6	LABEL	10*10mm	pcs	1
5			pcs	2
4	OUTER MOLD	50P PVC COLOR: BLACK	g	8
3	INNER MOLD	LD PE	g	8
2	CONNECTOR	HDM 19PIN MALE SOLDER INSULATION BLACK SHELL GOLD PLATED	pcs	2
1	CABLE	UL20276 (28AWG*1P+D+AL+MYLAR) *5C+4C*28AWG+AL+B CD. 7. 3 JACKET: BLACK High Speed HDMI Cable with Ethernet	mm	L

Pin Assignment

Conn. 1

Conn. 2

82584/ 82583/ 82454/ 82455		
REV: A/ 1	CUSTOMER:	DRAWN BY:
UNIT: mm	DWG NO.	CHECKED BY:
SCALE: NONE	PART NO.	APPROVED BY: