



WWW.DELOCK.COM

DATA SHEET



Slot bracket USB 3.0 pin header 19 pin 1 x internal > 2 x USB 3.0-A female external low profile

Description

This low profile slotblech by Delock is most suitable for installation into a PC slot of a mini PC and expands your system by two external USB 3.0-A ports. Thus you can connect different USB 3.0 devices, like e.g. external enclosure, Card reader, memory etc. Since the USB 3.0-A interface is compatible to its forerunners USB 2.0 and USB 1.1, you can still use your existing USB devices.



Ref. 82976

EAN 4043619829767

Country of origin China
Customs tariff number 84718000

Images

Specification

- Connector: internal 4 x USB 3.0-A male external 4 x USB 3.0-A female
- Cable gauge: 28 AWG
- · Current output: max. 900 mA per each USB port
- Voltage: 5 V
- Data transfer rate up to: Super-Speed 5 Gb/s,

High-Speed 480 Mb/s, Full-Speed 12 Mb/s, Low-Speed 1.5 Mb/s

- Downwards compatible to USB 2.0 and USB 1.1
- Cable length: ca. 40 cm (without connector)

System requirement

- · PC with a free slot
- PC with four free USB 3.0 Ports

Note: For operation of four devices at the same time, which require more than 900 mA for each device, you may need to connect an additional power supply for the connected device.

Package content

Slot bracket

Package

Delock poly bag

© 2011 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.