

Delock

Descripción



Especificación técnica

- Connectors:
 - 1 x SFP slot for 1000Base-X SFP module (SFP module not included)
 - 1 x RJ45 jack for 10/100/1000 Mb/s Base-T (PoE+)
 - 1 x DC female 5.5 x 2.1 mm (power)
- Data transfer rate up to 1 Gb/s
- 6 LEDs for status monitoring
- LFP (Link Fault Passthrough)
- Supports IEEE 802.3 / 802.3u / 802.3ab / 802.3z
- Supports IEEE 802.3at (PoE+) and 802.3af (PoE)
- Spare-Pairs power transmission (Mode B, pairs 4/5 and 7/8)
- Power output: max. 30 W
- Metal housing
- Fanless
- Operating temperature: -20 °C ~ 60 °C
- Dimensions (LxWxH): ca. 95 x 71 x 26 mm

Especificaciones de la fuente de alimentación

- Power supply with IEC connector
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.0 A
- Output: DC 48 V / 1.25 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9 mm

Requisitos del sistema

- 1000Base-X SFP module
- Device with one free RJ45 port

Contenido del paquete

- PoE Medienkonverter
- Netzteil
- Netzkabel
- Bedienungsanleitung

Número de elemento 86180

EAN: 4043619861804

Pais de origen: China

Paquete: White Box





Image





Interface	
Salida:	1 x RJ45 female (PoE)
Entrada:	1 x 5 V DC female 5,5 mm x 2,1 mm 1 x SFP slot
Technical characteristics	
Velocidades de transferencias de datos: Gigabit Ethernet up to 1 Gbps	
Physical characteristics	
Housing colour:	negro
Housing material:	metal
Length:	95 mm
Width:	70 mm
Height:	26 mm
Power supply	
Type:	Power supply with IEC connector
Input:	AC 100 - 240 V / 50 - 60 Hz / 2.0 A
Output:	48 V / 1.25 A
Connector:	DC male 5.5 mm x 2.1 mm