

1. Test:
1. 100% short circuit, open circuit and dislocation test;
2, conduction impedance: 3 ω (Max)
3, field measurement: A.) field measurement C correct reverse identification hard disk
B.) Whether the measured disk transmission speed reaches USB3.1, The read/write data must be at least 300MB/S



NO	ITEM	DESCRIPTION	Q'TY	UNIT
⑩		Wire clip 30+32+26+34AWG	2	pcs
⑨		High temperature adhesive tape	0.07	M
⑧		Double conductive copper foil	0.08	M
⑦		USB TYPE C on Meta Can	2	pcs
⑥		USB TYPE C Under the Meta Can	2	pcs
⑤		45P Black PVC	12	g
④		Low pressure forming material ~	1	g
③		山USB 3.1 C Type Connector PCB+SMT+10NF Capacitance Nickel plating	1	pcs
②		3.1 C Type Connectorr PCB+SMT+10NF Capacitance+IC Nickel plating	1	pcs
①		USB3.1~[30AWG(7/0.1TC)+EAM]*4P+[31AWG(7/0.08TC)+EA]*1P+26AWG(7/0.16TC)*2C+[34AWG(7/0.06TC)+A]*3C +34AWG(7/0.06TC)*1C+A2EB(24/11/0.06TC 85%)OD:5.2MM~black	2.01	M

REV.	ECN NO	DESCRIPTION	DATE	NAME

TOLERANCE	INCHES	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

DRAWN BY	Shijie	CUSTOMER :	
CHECK BY		CUSTOMER P/N :	AC7402
APPD BY		SCALE	NONE
		UNIT	MM
		DATE	2021.11.15

TITLE: USB3.1 CM TO CM(E-Mark) 5G 3A L=2M

DRAWING NO.: REV. A0

1/3



4、Pin Assignment:





REV.	ECN NO	DESCRIPTION	DATE	NAME

TOLERANCE	INCHES	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

TITLE:	USB3.1 CM TO CM(E-Mark) 5G 3A L=2M
DRAWN BY	Shijie
CUSTOMER :	
CUSTOMER P/N :	AC7402
CHECK BY	
APPD BY	
SCALE	NONE
UNIT	MM
DATE	2021.11.15
DRAWING NO.:	
REV.	A01
	2/3

NO	ITEM	DESCRIPTION	Q'TY	UNIT

Notice of USB–IF Certification

Date: 2022-05-16

TID 7697, listed as Marketing Name: USB 3.2 Gen1 USB-C TO USB-C 2M/3A Cable With E-Mark Part Number: AC7402 has passed USB–IF Compliance testing and is listed on the Integrators list as certified by ACT. Testing for this product was performed at Allion Labs, Inc. - Taiwan.

The most current information is always posted on the Integrators List at www.usb.org. Please feel free to contact admin@usb.org if you have any questions.

USB–IF Administration