




ITEM	PART	DESCRIPTION
A + B	Connector type	HDMI A male
	Contacts	Gold plated
	Hood	Molded plastic
	Shield type	Aluminum Mylar
	Conductor material	Copper
C	Cable colour	Black
	Outer jacket	PVC
D	Wire gauge	30 AWG
	Outer diameter	Ø6.0 ±0.2mm
	Bend radius	40mm
	Temperature range	-20°C to +70°C (+5%)
	Humidity range	45% to 65%
	Max. bandwidth	18 Gb/s
	HDMI version	2.0
	HDMI standard	HDMI High Speed
	Max. resolution @ 60Hz	3840 x 2160 (4K)
	Chroma sampling	4:2:0
	Colour bit depth	8 bits per colour
D	Protective cap	PE

Item No.	Length
AK3900	0.5m
AK3901	1.0m
AK3917	1.5m
AK3902	2.0m
AK3903	3.0m
AK3904	5.0m

ACT

Drawn by : EP


High Speed cable v2.0 HDMI-A male - HDMI-A male

Item : AK390x

Revision : 01-AA

Date : 13-07-2023

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.



ITEM	PART	DESCRIPTION
A + B	Connector type	HDMI A male
	Contacts	Gold plated
	Hood	Molded plastic
	Shield type	Aluminum Mylar
	Conductor material	Copper
C	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	28 AWG
	Outer diameter	Ø7.3 ±0.2mm
	Bend radius	40mm
	Temperature range	-20°C to +70°C (+5%)
	Humidity range	45% to 65%
	Max. bandwidth	18 Gb/s
	HDMI version	2.0
	HDMI standard	HDMI High Speed
	Max. resolution @ 60Hz	3840 x 2160 (4K)
	Chroma sampling	4:2:0
	Colour bit depth	8 bits per colour
D	Protective cap	PE

ACT

Drawn by : EP


7 meters High Speed cable v2.0 HDMI-A male - HDMI-A male

Item : AK3905

Revision : 01-AA

Date : 06-12-2023

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.



ITEM	PART	DESCRIPTION
A + B	Connector type	HDMI A male
	Contacts	Gold plated
	Hood	Molded plastic
	Shield type	Aluminum Mylar
	Conductor material	Copper
C	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	26 + 28 + 26 AWG
	Outer diameter	Ø8.0 ±0.2mm
	Bend radius	40mm
D	Temperature range	-20°C to +70°C (+5%)
	Humidity range	45% to 65%
	Max bandwidth	18 Gb/s
	HDMI version	2.0
	HDMI standard	HDMI High Speed
	Max. resolution @ 30Hz	3840 x 2160 (4k)
	Chroma sampling	4:2:0
	Color bit depth	8 bits per colour
D	Protective cap	PE

ACT

Drawn by : EP

15 meters High Speed cable v2.0 HDMI-A male - HDMI-A male (AWG28)

Item : AK3918

Revision : 01-AA

Date : 06-12-2023

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.