
# 6-Port Multi-Gigabit Unmanaged Switch

Turbocharged multi-gig switch for work or play

# DMS-106XT

- Full 2.5 Gbps Ethernet ports for unrestricted Wi-Fi 6 router or AP connections
- 10 Gbps port for NAS or Uplink connectivity
- Auto Speed Detection (1000 /2500/5000/10000 Mbps)
- Smart Turbo Mode delivers low latency performance for gaming and 4K streaming<sup>1</sup>
- First-rate power efficiency
- Fanless operation
- Industry-leading premium and durable aluminum alloy housing







### Turbo Mode

Activate Turbo Mode whenever you're ready for optimized performance



**Metal Casing** 

Rugged aluminum alloy matte gray casing



**Plug and Play** Ready to perform right out of the

box with no configuration required



**Multi-Gigabit** Multi-Gigabit ports for

Multi-Gigabit ports for high data rate transmission



Multicolored LED

Multi-Colored LED light conveniently indicates Turbo Mode status



Power Efficiency

Designed for low power consumption (10.6 W)



## **Silent Operation**

Fanless design enhances reliability and is suitable for noise-free working environments



**QoS** Management

Quality of Service for uninterrupted connections

Model	DMS-106XT
Product Image	
General	
Hardware Version	A1
Interfaces	5 x 10/100/1000/2500Mbps ports 1 x 10/100/1000/2500/5000/10000Mbps port
Standards	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x Flow Control IEEE 802.1p QoS IEEE 802.3az Energy-Efficient Ethernet (EEE) IEEE 802.3bz 2.5G/5G Base-T IEEE 802.3an 10G Base-T
Media Interface Exchange	Auto or configurable MDI/MDIX
LED	Per port: Link/Activity Per device: Power
Functionality	
Switching Capacity	35 Gbps switching fabric
Transmission Method	Store-and-Forward
MAC Address Table	4К
Packet Filtering/ Forwarding Rates	Gigabit Ethernet:1,488,000 pps per port
Physical	
Power Input	DC 12V / 1.5A (100-240 V)
Maximum Power Consumption	10.6 W

## **Order Information**

Heat Dissipation

**Operating Temperature** 

Storage Temperature Operating Humidity

Dimensions (L x W x H)

Storage Humidity

MTBF

Weight

DMS-106XT

EMI

6-Port N

6-Port Multi-Gigabit Unmanaged Switch

217 x 163 x 33 mm (8.54 x 6.42 x 1.30 in)

CE, FCC, RCM, BSMI, VCCI, RoHS

<sup>1</sup> Activate Turbo Mode to keep your entertainment services such as online gaming and 4K video streaming at maximum network speeds with port-based QoS and IGMP Snooping.

#### HQ | No. 289, Xinhu 3rd Road, Neihu District, Taipei 11494

Specifications are subject to change without notice. © 2020 D-Link. All Rights Reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link. All other third-party marks mentioned herein may be trademarks of their respective owners.

36.17 BTU/h

489,941 hours 0 - 40 °C (32 - 104 °F)

10% - 95% RH

5% - 95% RH

680 g

-10 - 70 °C (14 - 158 °F)



/ DMS-106XT