




SCALE 2/1

SCALE 1/1

Specification :

Adaptor	Type	Color
MTP	SC Footprint A Type(Up to Down)	Black
LC	Zirconia	Aqua

	Type
Direct Harness (12C)	OM3, 0.9mm Jacket, PVC, 12F MTP+Guide Pin, LC(MM), Low Loss

LC	Straight Version	MTP
1	←→	1
2	←→	2
3	←→	3
4	←→	4
5	←→	5
6	←→	6
7	←→	7
8	←→	8
9	←→	9
10	←→	10
11	←→	11
12	←→	12

LC Fiber Number	Jacket Color	Fiber Position	MTP Fiber Number
Fiber 1	Blue	B	Fiber 1
Fiber 2	Orange	A	Fiber 2
Fiber 3	Green	B	Fiber 3
Fiber 4	Brown	A	Fiber 4
Fiber 5	Gray	B	Fiber 5
Fiber 6	White	A	Fiber 6
Fiber 7	Red	B	Fiber 7
Fiber 8	Black	A	Fiber 8
Fiber 9	Yellow	B	Fiber 9
Fiber 10	Purple	A	Fiber 10
Fiber 11	Pink	B	Fiber 11
Fiber 12	Aqua	A	Fiber 12

- a. Dimension: 1.18" x 2.95" x 5.12"
(30.0 x 75.0 x 130.0mm)
b. Weight: 0.23kg.
c. Surface Finished: Painted, BK(RAL9005)

"#": Matching DIM.
"*": Important DIM.
Others General DIM.

GENERAL TOLERANCE OF DIMENSIONS

X.XXX	±0.005
X.XX	±0.05
X.X	±0.1


DRAWING	05.NOV.2018	YMN
CHECK	05.NOV.2018	DAY
APPROVAL	05.NOV.2018	FRANK
DATE		NAME
SCALE	1/1 (A4)	UNIT mm
DRAWING NO.		LGX Cassette Method A&C 1x12F MTP to 12xLC OM3(S02)
DRAWING CLASSIFICATION		S SHEET 1 OF 2

ITEM NO.: FA2060

DES.: LGX Cassette Method A&C 1x12F MTP to 12xLC OM3(S02)

02






Specification :

Material :


- Connector Type : MTP Male(With Pin) Connector, Multimode Low Loss.
1-1. Protective Cap : TPR, Black color.
1-2. MT Ferrule : 12 Fibers, PPS, Black color, Multimode Low Loss.
1-3. MTP Housing : PBT, Aqua color.
- Connector Type : LC Multimode Low Loss, Ivory Color.
2-1. Protective Cap : PE, White color.
2-2. Ferrule : $\varnothing 1.25\text{mm}$, Zirconia, Singlemode.
2-3. LC Housing : PC, Ivory color.
2-4. Strain Relief Boot : PVC, White color.
- Shrink Tube : 1.5cm, Use Black Heat Shrink Tube.
- Tubing Type:
4-1. Fiber : OM3 50/125um Multimode.
4-2. 12 tubes Hytrel material, 0.9mm tube of 12 Colors.
- Fanout MTP(Male) to LC OM3 12C Patch cord 30cm.
1(Blue)/2(Orange)/3(Green)/4(Brown)/5(Gray)/6(White)/7(Red)/8(Black)/9(Yellow)/10(Purple)/11(Pink)/12(Aqua).

Performance :

- Insertion Loss :
LC MM Low Loss : $< 0.15\text{ dB}$
MTP MM Low Loss : $< 0.35\text{ dB}$
- Return Loss :
LC MM Low Loss : $> 35\text{ dB}$
MTP MM Low Loss : $> 20\text{ dB}$
- Fiber Extention(LC) : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- Fiber overcut(MTP) : $1\sim 3\mu\text{m}$
- Apex Offset : $< 50\mu\text{m}$
- Operating Temperature : -20°C to $+70^{\circ}\text{C}$
- Storage Temperature : -40°C to $+80^{\circ}\text{C}$



Connector Section (SCALE 3/1)

"##": Matching DIM. "*: Important DIM. Others General DIM.	DRAWING	05.NOV.2018	YMN					
	CHECK	05.NOV.2018	DAY					
	APPROVAL	05.NOV.2018	FRANK					
GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1			DATE	NAME	ITEM NO.: FA2060			
	SCALE	1/1 (A4)	UNIT	mm	DES.: LGX Cassette Method A&C 1x12F MTP to 12xLC OM3			
		DRAWING NO.		LGX Cassette Method A&C 1x12F MTP to 12xLC OM3(S02)				
		DRAWING CLASSIFICATION			S	SHEET	1 OF 1	