

- NOTE:
1. INSERTION LOSS < 0.3dB.
 2. OPERATION TEMP: -25°C TO +80°C, 5 CYCLES.
 3. DURABILITY: 500 CYCLES.
 4. VIBRATION: 10 TO 55 Hz 1.5mm DOUBLE AMPLITUDE.
 5. TENSILE STRENGTH: 10Kg.
 6. PACKING:


SEE TABLE "DESCRIPTION 1"

PO/NO.:




SEE TABLE "DESCRIPTION 2"

ROUND CABLE METHOD SEE "DETAIL A"		
BAG TYPE	QTY	LABEL
SMALL	POLYBAG	1 CABLE WITH TEST CARD SEE "DETAIL C"
MEDIUM	POLYBAG	5 CABLES
LARGE	POLYBAG	ALL
EACH LARGE POLYBAG IN AN OUTER CARTON		



DETAIL A



DETAIL B

Y: Year, mm: Month
xxxxx: Serial Number

ATG Fiber Optical Patchcord

ST/PC to ST/PC Duplex Multimode 62.5/125, OM1, Ø3.0mm *M-RoHS

Model: xxxxx-xxxxxx

Lot number: xxxxxxxx

Performance: (@23°C) λ=850/1310±20nm

Insertion Loss ≤ 0.3dB

Serial No

A	850nm	1310nm
B		
C		
D		

Kymxxxxxx

Prepared By: _____ Date: _____

DETAIL C

RL1005	5	16.4'(5000)	112205-RL1005	8716065170757
RL1003	3	9.84'(3000)	112203-RL1003	8716065170740
RL1002	2	6.56'(2000)	112202-RL1002	8716065170733
RL1001	1	3.28'(1000)	112201-RL1001	8716065170726
PART NO.	*	L	DESCRIPTION 1	DESCRIPTION 2

CUSTOMER APPROVAL:

DATE:



3	4PCS	ST DUST COVER, CLEAR.	
2	2SETS	CONNECTOR: ST/PC MM, WITH 3.0mm BLACK & RED BOOT.	
1	1PC	CABLE: MULTIMODE, 62.5/125um, 3.0mm ZIPCORD, OFNR, ORANGE JACKET.	
ITEM	QTY	PART NO.	DESCRIPTION
PART LIST			

	UNIT: Inches[mm]	TITLE: PATCHCORD ST-ST MULTIMODE DUPLEX 62.5/125, OM1, 3.0mm, ORANGE.
DRAWN BY Catherine	DATE 2007/10/3	CUSTOMER
CHECKED BY	DATE	CUSTOMER PART NO.
APPROVED BY	DATE	DRAWING NO. PK709001
SCALE BY	DATE	Ref. NO. REV. B