

TPOS

Fanless zero bezel 15" POS Terminal



LONGSHINE's TPOS was designed for applications which require high performance and installation feasibilities. Through it's high degree of adjustable operation angles, it adapts to maximal installation environments. Your total cost of ownership will also be significantly reduced through competitive hardware costs, improved efficiencies and minimal administration efforts. Finally, high product quality ensures a long lifecycle.

Maximise the usage, minimize the cost

Platforms Quad Core covers all needs

- Flexibility of power

IP-65 and zero bezel design

Zero bezel and none ventilation hole at the back for reliability

- IP-65 water and dust proof sealing for industrial usage

New feasible compact design

Easily configured on the counter to suit maximal demands of the user

- Designed for maximal installation environments

Fanfree design

- Contributes to a pleasant quiet working environment

Performance

Fits into any POS software environment with relative ease


- TPOS provides a wide range of platforms to cover all software needs

Construction variety

- Benefit from the advantages of various constructions



Dimensions:



Technical Specifications:

Model		TPOS-PV5F
CPU	INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor	
I.O Chipset	INTEL IT8782F	
Memory	4GB Standard (DDR3L / SO-DIMM slot x 1); maximal capacity up to 8GB	
Expansion Slots	2 * MiniPCI-E connector slot	
Ethernet LAN	Realtek® RTL8111F Chip; PCI Express Gigabit LAN	
Audio	ALC662 Audio CODEC; HD Audio CODEC	
Storage	1 x 64GB SSD	
Display		
TFT LED Panel	15” 250nits Typ.,1024 x 768 resolution	
Touch Screen	P-Cap type	
Touch Control Board	USB interface	
External I/O Ports		
USB Port	1* USB 3.0 port; 6* USB 2.0 ports	
Network (LAN)	1* RJ-45 GigaLAN	
Audio Port	1* Line-out connector	
Display Port	1 * VGA port	
Serial Port	3 * D-SUB9; COM1/2 with +5V/12V power selectable	
Power Input	1* 12V DC in	
Optional Peripherals		
Customer Display	VFD Type: 20 columns x 2 lines, each column 5x7 dots 7”~10” Dual Display (VESA HOLE 75x75)	
i-Button	Read all Dallas Touch Memory Buttons (Support output Interfaces for USB HID and USB Virtual COM Interface	
MSR	JIS-I or II, ISO Track 1/2/3 USB (default)	
Operation System		
	Windows 7, Linux (Ubuntu, Fedora), POS-Ready 7, Windows 8, Windows 10	

Features and specifications are subject to change without prior notice.

CONTACT

LONGSHINE Technologie GmbH
 No 945 Boai Street, Jubei City, Hsinchu, Taiwan 30265
 An der Strusbek 9, 22926 Ahrensburg, Germany
 TEL: +49 4102 49220 FAX: +49 4102 40109
 www.longshine.de

All rights reserved, including intellectual property rights. Changes to technical data reserved.
 Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is excluded. Copyright © 1981-2017 LONGSHINE Technologie GmbH.